

## PENTEK ELPC STANDARD SERIES ELECTROPLATING CARBON CARTRIDGES

A UNIQUE BLOCK WITH TRUE DEPTH FILTRATION CAPABILITY

---



**Pentair<sup>®</sup> Pentek<sup>®</sup> ELPC Series Cartridges is a premium line of activated carbon filter cartridges specifically designed for electroplating solutions. They represent the best technology available in cartridge filtration for use in a wide range of electroplating applications.**

**The unique technology used to manufacture this product ensures that there is no bleeding of carbon fines into the plating bath. In addition, the carbon that is used is an ultra-clean, highly purified carbon to ensure that sulfur is not leached into the plating bath.**

**Pentek ELPC Series products have a 7-micron nominal rating with superior dirt-holding ability.**

**The fibrous physical structure created by our proprietary Fibredyne technology produces a unique block with true depth filtration capability which allows for maximum treatment with minimal pressure drop through the cartridge.**

### FEATURES/BENEFITS

---

Cellulose-free construction

Resistant to chemical breakdown in both acidic and alkaline solutions up to 180°F (82°C)

Integrated post-filtration layer to ensure that no carbon fines are bled into the plating bath

Endcap gaskets are permanently molded on to the endcaps to ease filter cartridge change-out

### SPECIFICATIONS

---

Filter Media – Bonded PAC

Endcaps – Polypropylene

Netting – Polypropylene

Gaskets - Santoprene

Temperature Rating –  
40-180°F (4.4-82.2°C)

## SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (NOMINAL)	INITIAL (PSI) @ FLOW RATE (GPM)
ELPC-10*	255668-43	2.88" x 10" (73 mm x 254 mm)	7	3.4 psi @ 1 gpm (0.23 bar @ 3.8 Lpm)
ELPC-20	255669-43	2.88" x 20" (73 mm x 508 mm)	7	3.4 psi @ 2 gpm (0.23 bar @ 7.6 Lpm)
ELPC-30	255670-43	2.88" x 30" (73 mm x 762 mm)	7	3.4 psi @ 3 gpm (0.23 bar @ 11.4 Lpm)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the unit.

NOTE: Cartridges will contain a very small amount of carbon fines (very fine black powder). After installation, a new cartridge should be flushed with sufficient water to remove all traces of fines prior to using the water.

NOTE: Micron ratings based on 85% or greater removal of given particle size. Estimated capacity using 2 ppm free available chlorine at 0.5 ppm breakthrough.

\* The ELPC-10 will not fit #10 Slim Line or #10 Standard housings.



### WATER QUALITY SYSTEMS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2015 Pentair Residential Filtration, LLC. All rights reserved.

†For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com](http://waterpurification.pentair.com).

Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

310115 REV C MY15